

What Is Claimed Is:

1 1. A method for detecting a denial-of-service attack using an
2 execution profile for a kernel of a server computer system, comprising:
3 producing a run-time execution profile by gathering statistics related to
4 execution of a protocol stack within the kernel of the server;
5 wherein the protocol stack processes packets received from client
6 computer systems;
7 comparing the run-time execution profile with a normal execution profile
8 for the kernel of the server;
9 wherein the normal execution profile is representative of execution when
10 the server is not subject to a denial-of-service attack; and
11 indicating that a denial-of-service attack is taking place if the run-time
12 execution profile deviates from the normal execution profile.

1 2. The method of claim 1, wherein producing the run-time execution
2 profile involves gathering statistics regarding a fraction of time that the server
3 spends executing one or more portions code related to the protocol stack.

1 3. The method of claim 2, wherein producing the run-time execution
2 profile involves producing a vector indicating a number of times that the server is
3 found to be executing the one or more portions of code related to the protocol
4 stack.

1 4. The method of claim 2, wherein the one or more portions of code
2 related to the protocol stack include:
3 a portion related to processing TCP SYN requests;

3 execution profile deviates more than a pre-specified amount from the normal
4 execution profile.

1 10. A computer-readable storage medium storing instructions that
2 when executed by a computer cause the computer to perform a method for
3 detecting a denial-of-service attack using an execution profile for a kernel of a
4 server computer system, the method comprising:
5 producing a run-time execution profile by gathering statistics related to
6 execution of a protocol stack within the kernel of the server;
7 wherein the protocol stack processes packets received from client
8 computer systems;
9 comparing the run-time execution profile with a normal execution profile
10 for the kernel of the server;
11 wherein the normal execution profile is representative of execution when
12 the server is not subject to a denial-of-service attack; and
13 indicating that a denial-of-service attack is taking place if the run-time
14 execution profile deviates from the normal execution profile.

1 11. The computer-readable storage medium of claim 10, wherein
2 producing the run-time execution profile involves gathering statistics regarding a
3 fraction of time that the server spends executing one or more portions code related
4 to the protocol stack.

1 12. The computer-readable storage medium of claim 11, wherein
2 producing the run-time execution profile involves producing a vector indicating a
3 number of times that the server is found to be executing the one or more portions
4 of code related to the protocol stack.

095507.09304
T0260.406660

1 13. The computer-readable storage medium of claim 11, wherein the
2 one or more portions of code related to the protocol stack include:
3 a portion related to processing TCP SYN requests;
4 a portion related to processing TCP ACKs;
5 a portion related to processing TCP data;
6 a portion related to processing ICMP echo requests; and
7 a portion that is unrelated to the protocol stack.

1 14. The computer-readable storage medium of claim 10, wherein the
2 method further comprises producing the normal execution profile by gathering
3 statistics related to execution of the server when the server is not subject to a
4 denial-of-service attack.

1 15. The computer-readable storage medium of claim 10, wherein if a
2 denial-of-service attack is detected, the method further comprises blocking
3 offending packets from reaching the server.

1 16. The computer-readable storage medium of claim 10, wherein
2 producing the run-time execution profile involves gathering statistics over a first
3 time window, and subsequently gathering statistics for a subsequent run-time
4 execution profile over a second time window.

1 17. The computer-readable storage medium of claim 16, wherein the
2 method further comprises gathering statistics for a concurrent execution profile
3 over a concurrent time window that overlaps the first time window and the second

4 time window, so that a denial-of service attack that overlaps the first time window
5 and the second time window can be detected in the concurrent time window.

1 18. The computer-readable storage medium of claim 10, wherein
2 comparing the run-time execution profile with the normal execution profile
3 involves determining if the run-time execution profile deviates more than a pre-
4 specified amount from the normal execution profile.

1 19. A apparatus that detects a denial-of-service attack through use of
2 an execution profile for a kernel of a server computer system, comprising:
3 a profiling mechanism that is configured to produce a run-time execution
4 profile by gathering statistics related to execution of a protocol stack within the
5 kernel of the server;
6 wherein the protocol stack processes packets received from client
7 computer systems;
8 a comparison mechanism that is configured to compare the run-time
9 execution profile with a normal execution profile for the kernel of the server;
10 wherein the normal execution profile is representative of execution when
11 the server is not subject to a denial-of-service attack; and
12 wherein the comparison mechanism is configured to indicate that a denial-
13 of-service attack is taking place if the run-time execution profile deviates from the
14 normal execution profile.

1 20. The apparatus of claim 19, wherein the profiling mechanism is
2 configured to gather statistics regarding a fraction of time that the server spends
3 executing one or more portions code related to the protocol stack.

1 26. The apparatus of claim 25, wherein the profiling mechanism is
2 additionally configured to gather statistics for a concurrent execution profile over
3 a concurrent time window that overlaps the first time window and the second time
4 window, so that a denial-of service attack that overlaps the first time window and
5 the second time window can be detected in the concurrent time window.

1 27. The apparatus of claim 19, wherein the comparison mechanism is
2 configured to determine if the run-time execution profile deviates more than a pre-
3 specified amount from the normal execution profile.